NSN 5935-01-483-2228



Electrical Receptacle Connector - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5935-01-483-2228 **Thread Class:** 2a and 2a **Thread Direction:** Right-hand and right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 2.125 inches **Overall Height:** 1.750 inches **Overall Width:** 1.750 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 1.375 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.375 inches **Distance From Mounting Shoulder To Front Face:** 0.812 inches **Threaded Device Type:** Coupling facility and back shell **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 24-2 single mating end **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Key or multiple key **Insert Position In Deg:** 0.0 Shell Type: **Connector Locking Method:** Externally threaded shell **Thread Size:** 1.500 inches and 1.4375 inches **Terminal Location:** Back single mating end single contact grouping

Terminal Type:
Crimp single ma

Crimp single mating end single contact grouping

Shell Material:

Aluminum alloy

NSN 5935-01-483-2228

Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment:
Cadmium
Included Contact Quantity:
7 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Color:
Olive drab
Precious Material And Location:
Contact surface gold
Precious Material:
Gold
Thread Series Designator:
Unef and unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-dtl-5015 spec.