

View Online at <https://aerobasegroup.com/nsn/5935-01-484-0132>

Body Style:

Straight shape, flush mount

Overall Length:

0.954 inches

Overall Height:

3.110 inches

Overall Width:

2.000 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

2.783 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.437 inches

Distance From Mounting Shoulder To Front Face:

0.766 inches

Mating End Quantity:

2

Contact Position Arrangement Style:

57m 2nd mating end

Contact Removability:

Removable all mating ends all contact groupings

Polarization Method:

3 polarization posts

Shell Type:

Solid

End Application:

Otps-3, vast; cass

Terminal Location:

Back all mating ends all contact groupings

Contact Material:

Copper alloy all mating ends all contact groupings

Contact Surface Treatment:

Gold all mating ends all contact groupings

Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response all mating ends all contact groupings

Terminal Type:

Solder well all mating ends all contact groupings

Contact Material Specification:

Qq-c-533 federal standard single material response all mating ends all contact groupings

Guide Design And Location:

Hexagon shape male post left-hand at 12 oclock and hexagon shape male post center at 12 oclock and hexagon shape male post right-hand at 12 oclock

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium and chromate

Shell Surface Treatment Specification:

Qq-p-416 federal standard all treatment responses

Shell Material Specification:

Qq-a591 federal standard single material response and qq-a-380 federal standard single material response

Included Contact Quantity:

57 2nd mating end single contact grouping

Included Contact Type:

Round socket 2nd mating end single contact grouping

Special Features:

Floating eyelets

Precious Material And Location:

Contact surfaces gold

Precious Material:

Gold

Supplementary Features:

Mounting method - float

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.