NSN 5935-01-485-0802

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-485-0802 **Body Style:** Straight shape, external coupling Overall Length: 1.417 inches Overall Diameter: 0.687 inches **Distance From Mounting Shoulder To Front Face:** 0.414 inches **Mounting Facility Thickness:** 0.006 inches **Mating End Quantity: Contact Position Arrangement Style:** Bnc single mating end **Contact Maximum Ac Voltage Rating In Volts:** 500.0 single mating end single contact grouping **Contact Maximum Frequency Rating:** 4.0 gigahertz single mating end single contact grouping Shell Type: Solid **Connector Locking Method:** Bayonet pin Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 single mating end single contact grouping **End Application:** Next generation radar (nexrad) **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper single mating end single contact grouping or copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Terminal Type:** Crimp single mating end single contact grouping **Shell Material:** Copper alloy **Shell Surface Treatment:** Nickel and silver **Shell Surface Treatment Specification:**

Shell Material Specification:

Qq-b-626 federal specification single material response

Mil-c-39012 military specification all treatment responses

NSN 5935-01-485-0802

Electrical Receptacle Connector - Page 2 of 2



Included Contact Quan	tity:
-----------------------	-------

1 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surface gold and body silver

Precious Material:

Gold and silver

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-c-39012 spec.