Electrical Connector Backshell - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5935-01-485-3392

| Tł | nread Class: |
|----|---|
| 2a | 1 |
| Tł | nread Direction: |
| Ri | ght-hand |
| 0 | verall Length: |
| 1. | 500 inches |
| 0 | verall Diameter: |
| 1. | 730 inches |
| Er | nd Application: |
| C | 0890, panavia aircraft |
| Са | able Opening Quantity: |
| 1 | |
| Si | ze Designation: |
| 24 | L Contraction of the second |
| M | ounting Facility Type And Quantity: |
| 1 | threaded coupling |
| Tł | nready Qty Per Inch (tpi): |
| 18 | 3 |
| Tł | nread Size: |
| 1. | 438 inches |
| M | aterial: |
| AI | uminum alloy |
| Sı | urface Treatment: |
| Са | admium and chromate and nickel |
| St | yle Designator: |
| St | raight type |
| Sı | urface Treatment: |
| Са | admium and chromate and nickel, electroless |
| Tł | nread Series Designator: |
| Uı | nef |
| Sł | nelf Life: |
| N/ | la l |
| U | nit Of Measure: |
| | |
| De | emilitarization: |
| No | 0 |
| Fi | ig: |
| A٢ | 10100 |