## NSN 5935-01-485-9698

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-485-9698 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.300 inches **Overall Height:** Between 1.173 inches and 1.203 inches **Overall Width:** Between 1.173 inches and 1.203 inches **Unthreaded Mounting Hole Diameter:** 0.125 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.938 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.938 inches **Distance From Mounting Shoulder To Front Face:** 0.625 inches **Threaded Device Type:** Back shell **Mating End Quantity: Contact Position Arrangement Style:** 13-oct single mating end **Contact Maximum Current Rating In Amps:** 3.0 single mating end single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 500.0 single mating end single contact grouping **Polarization Method:** Key, multiple key groove **Insert Position In Deg:** 0.0 **Connector Locking Method:** Externally threaded shell **End Application:** 

Amp/eq assembly, radar and iff systems

**Features Provided:** 

Color band engagement indicator

Thready Qty Per Inch (tpi):

24

## NSN 5935-01-485-9698

Electrical Receptacle Connector - Page 2 of 2



Thread Size:
0.625 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Shell Material:
Steel comp 316l
Shell Surface Treatment:
Passivate
Included Contact Quantity:
13 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact plating gold
Precious Material:
Gold
Supplementary Features:
Mounting method - unthreaded hole
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0