NSN 5935-01-486-9366

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-486-9366 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 2.500 inches **Overall Diameter:** 3.061 inches **Distance From Mounting Shoulder To Front Face:** 0.966 inches **Mounting Facility Thickness:** 0.128 inches **Threaded Device Type:** Back shell **Mating End Quantity: Contact Position Arrangement Style:** 40-9 single mating end **Contact Removability:** Removable single mating end all contact groupings **Polarization Method:** Key or multiple key **Insert Position In Deg:** 235.0 Shell Type: Solid **Connector Locking Method:** Externally threaded shell **End Application:** Mk74m0d1, vems Thready Qty Per Inch (tpi): 16 **Thread Size:** 2.500 inches **Terminal Location:** Back single mating end all contact groupings **Terminal Type:** Crimp single mating end all contact groupings **Shell Material:**

Aluminum alloy

NSN 5935-01-486-9366

Electrical Receptacle Connector - Page 2 of 2



| Shell Surface Treatment: |
|--|
| Cadmium |
| Included Contact Quantity: |
| 24 single mating end 1st contact grouping |
| Included Contact Type: |
| Round socket single mating end all contact groupings |
| Color: |
| Olive drab |
| Precious Material And Location: |
| Contact surfaces gold |
| Precious Material: |
| Gold |
| Supplementary Features: |
| Mounting method - jam mut |
| Thread Series Designator: |
| Un |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A039b0 |
| |