## NSN 5935-01-487-8545

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-487-8545

**Body Style:** 

Straight shape, external coupling

**Overall Length:** 

1.039 inches

**Overall Height:** 

Between 1.219 inches and 1.239 inches

**Overall Width:** 

Between 1.219 inches and 1.239 inches

**Environmental Protection:** 

Moisture proof and salt water resistant and vibration proof

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.484 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.484 inches

**Distance From Mounting Shoulder To Front Face:** 

Between 0.815 inches and 0.820 inches

**Mating End Quantity:** 

1

**Contact Position Arrangement Style:** 

15-35 single mating end

**Polarization Method:** 

Keyway or multiple keyway

**Insert Position In Deg:** 

265.0 and 220.0 and 132.0 and 105.0 and 326.0

Shell Type:

Solid

**Connector Locking Method:** 

Bayonet pin

**End Application:** 

B-52 aircraft

**Terminal Location:** 

Back single mating end single contact grouping

**Terminal Type:** 

Crimp single mating end single contact grouping

**Shell Material:** 

Aluminum alloy

**Shell Surface Treatment:** 

Cadmium

**Included Contact Quantity:** 

35 single mating end single contact grouping

**Test Data Document:** 

81349-mil-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## NSN 5935-01-487-8545

Electrical Receptacle Connector - Page 2 of 2



Spec	ific	ation	Data:
------	------	-------	-------

96906-ms27505 government standard

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A039b0

Mil-std (military Standard):

Mil-c-38999 spec.