Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-493-3206

### **Body Style:**

Right angle type

### **Overall Length:**

6.400 inches

### **Overall Height:**

0.550 inches

#### **Overall Width:**

0.522 inches

#### **Environmental Protection:**

Vibration resistant and shock resistant and salt water resistant and humidity resistant and thermal shock resistant

### **Unthreaded Mounting Hole Diameter:**

0.120 inches

### **Distance Between Mounting Facility Centers:**

6.150 inches

### Mating End Quantity:

1

### **Contact Position Arrangement Style:**

3 rows of contacts non-inserted board single mating end

### Contact Removability:

Nonremovable single mating end single contact grouping

### **Contact Maximum Current Rating In Amps:**

5.0 single mating end single contact grouping

## **Polarization Method:**

Guide pin/socket

### **Connector Locking Method:**

Friction

### **Operating Tempurature Rating:**

Between -65.0 degrees celsius and 125.0 degrees celsius

### **Terminal Location:**

Side single mating end single contact grouping

### **Contact Material:**

Copper alloy single mating end single contact grouping

### **Contact Surface Treatment:**

Gold single mating end single contact grouping

### **Insert Material:**

Plastic diallyl phthalate glass filled single mating end

### **Terminal Type:**

Solder well single mating end single contact grouping

# Unable To Decode:

Unable to decode and unable to decode

# Included Contact Quantity:

160 single mating end single contact grouping



Included Contact Type:

Round pin single mating end single contact grouping

**Special Features:** 

Reverse guide set

**Precious Material And Location:** 

Contact surfaces gold

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A039b0