NSN 5935-01-493-3389

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-493-3389

Body Style:
Straight type
Overall Length:
6.400 inches
Overall Height:
0.335 inches
Overall Width:
0.350 inches
Environmental Protection:
Vibration resistant and shock resistant and salt water resistant and humidity resistant and thermal shock resistant
Unthreaded Mounting Hole Diameter:
0.120 inches
Distance Between Mounting Facility Centers:
6.150 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
3 rows of contacts non-inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Polarization Method:
Guide pin/socket
Connector Locking Method:
Friction
Operating Tempurature Rating:
Between -65.0 degrees celsius and 125.0 degrees celsius
Terminal Location:
Side single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate glass filled single mating end
Terminal Type:
Solder well single mating end single contact grouping
Unable To Decode:
Unable to decode and unable to decode

Included Contact Quantity:

160 single mating end single contact grouping

NSN 5935-01-493-3389

Electrical Receptacle Connector - Page 2 of 2



Included Contact Type: Round pin single mating end single contact grouping Special Features: Reverse guide set Precious Material And Location: Contact surfaces gold Precious Material: Gold Shelf Life: N/a Unit Of Measure: --Demilitarization: No

Fiig: A039b0