

View Online at <https://aerobasegroup.com/nsn/5935-01-493-3528>

Thread Class:

2a and 2a

Thread Direction:

Right-hand and right-hand

Body Style:

Straight shape, external coupling

Unable To Decode:

Unable to decode and unable to decode

Overall Length:

2.500 inches

Overall Diameter:

2.366 inches

Environmental Protection:

Corrosion resistant and humidity resistant and moisture resistant and salt water resistant and shock resistant and vibration resistant

Distance From Mounting Shoulder To Front Face:

0.970 inches

Mounting Facility Thickness:

0.128 inches

Threaded Device Type:

Back shell and coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

24-22 single mating end

Contact Removability:

Removable single mating end single contact grouping

Polarization Method:

Key or multiple key

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

End Application:

5411-01-436-3326

Thready Qty Per Inch (tpi):

18 and 18

Thread Size:

1.437 inches and 1.500 inches

Terminal Location:

Back single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium and nickel

Shell Surface Treatment Specification:

Qq-p-416 federal specification all treatment responses

Included Contact Quantity:

4 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Special Features:

CONT-AC-TSP-ERMI

Color:

Olive drab

Precious Material And Location:

Contact surfaces silver

Precious Material:

Silver

Supplementary Features:

Mounting method - jam nut

Test Data Document:

81349-mil-dtl-5015 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unef and unef

Specification Data:

96906-ms3454 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-dtl-5015 spec.