Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-493-7331

Body Style: Straight shape, external coupling **Overall Length:** 1.099 inches **Overall Height:** Between 1.418 inches and 1.458 inches **Overall Width:** Between 1.418 inches and 1.458 inches **Unthreaded Mounting Hole Diameter:** Between 0.123 inches and 0.138 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 1.156 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.156 inches

Distance From Mounting Shoulder To Front Face:

Between 0.815 inches and 0.820 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

19-32 single mating end

Polarization Method:

Key, multiple key groove

Insert Position In Deg:

0.0 and 95.0 and 132.0 and 232.0 and 260.0

Shell Type:

Solid

Connector Locking Method:

Bayonet pin

Terminal Location:

Back single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic epoxy single mating end

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium

Included Contact Quantity:

32 single mating end single contact grouping



Included Contact Type:

Round pin single mating end single contact grouping

Special Features:

Dms27505e19b32a fitted with pin contacts and capacitive filter array. Filter array attached to rear of connector and individual tails of contacts using high-temp solder, making it a fixed assembly.

Precious Material And Location:

Contant surfaces gold

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0