Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-494-8989

Thread Class:
2a
Thread Direction:
Right-hand and right-hand and right-hand
Body Style:
Straight shape, external coupling
Overall Length:
26.0 millimeters
Overall Diameter:
Between 44.2 millimeters and 44.8 millimeters
Environmental Protection:
Moisture proof and salt water resistant and vibration proof
Distance From Mounting Shoulder To Front Face:
16.7 millimeters
Mounting Facility Thickness:
Between 1.5 millimeters and 3.2 millimeters
Threaded Device Type:
Back shell and coupling facility and mounting bushing
Mating End Quantity:
1
Contact Position Arrangement Style:
17-35 single mating end
Contact Removability:
Removable single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0 and 80.0 and 142.0 and 196.0 and 293.0
Shell Type:
Solid
Connector Locking Method:
Externally threaded shell
End Application:
Communication junction box, 699-7000-01
Thread Size:
25.0 millimeters and 1.188 inches and 32.0 millimeters
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping



### **Terminal Type:**

Printed circuit single mating end single contact grouping

### Shell Material:

Aluminum alloy

# Shell Surface Treatment:

Cadmium

## Thread Tolerance Class:

6g external and 6g external

#### **Included Contact Quantity:**

55 single mating end single contact grouping

#### **Bushing Accommodation Hole Shape:**

Round w/flat

### Included Contact Type:

Round pin single mating end single contact grouping

#### **Special Features:**

D38999/24 connector supplied with printed circuit tails

### **Precious Material And Location:**

Contact surfaces gold

# Precious Material:

Gold

# **Thread Series Designator:**

Iso m and special acme and iso m

# Shelf Life:

N/a

## Unit Of Measure:

--

#### **Demilitarization:**

No

Fiig:

A039b0