Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-494-9715

Thread Class:

2b

Thread Direction:

Right-hand and right-hand and right-hand

Body Style:

Straight shape, external coupling

Overall Length:

32.5 millimeters

Overall Diameter:

38.1 millimeters

Environmental Protection:

Moisture proof and salt water resistant and vibration proof

Distance From Mounting Shoulder To Front Face:

22.6 millimeters

Mounting Facility Thickness:

Between 1.5 millimeters and 3.2 millimeters

Threaded Device Type:

Back shell and coupling facility and mounting bushing

Mating End Quantity:

1

Contact Position Arrangement Style:

13-35 single mating end

Contact Removability:

Removable single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0 and 113.0 and 156.0 and 182.0 and 292.0

Shell Type:

Solid

Connector Locking Method:

Internally threaded shell

End Application:

Communication junction box; 699-7000-01

Thready Qty Per Inch (tpi):

10

Thread Size:

18.0 millimeters and 0.875 inches and 25.0 millimeters

Thread Pitch In Millimeters:

1.00 and 1.00

Terminal Location:

Back single mating end single contact grouping

NSN 5935-01-494-9715 Electrical Receptacle Connector - Page 2 of 2



Contact Material: Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** Plastic epoxy single mating end **Terminal Type:** Printed circuit single mating end single contact grouping Shell Material: Aluminum alloy **Shell Surface Treatment:** Cadmium **Thread Tolerance Class:** 6g external and 6g external **Included Contact Quantity:** 22 single mating end single contact grouping **Bushing Accommodation Hole Shape:** Round w/flat Included Contact Type: Round pin single mating end single contact grouping **Special Features:** D38999/24 connector supplied with printed circuit tails **Precious Material And Location:** Contact surfaces gold **Precious Material:** Gold **Thread Series Designator:** Iso s and special acme and iso s Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A039b0