Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-495-8531

Body Style: Straight shape Overall Length: 0.870 inches Overall Height: 0.530 inches Overall Width: 0.340 inches Overall Width: 0.340 inches Distance Between Mounting Facility Centers: 0.625 inches Mating End Quantity: 1 Contact Position Arrangement Style: 11 single mating end Contact Removability: Nonremovable single mating end single contact grouping Polarization Method: Guide pin/socket Shell Type: Solid Ea-6b prowler aircraft Operating Tempurature Rating: Between -55.0 degrees celsius and 125.0 degrees celsius Terminal Location: Back single mating end single contact grouping Contact Material: Cooper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping Charter Well single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping <	
Overall Length:0.870 inchesOverall Height:0.530 inchesOverall Width:0.340 inchesDistance Between Mounting Facility Centers:0.625 inchesMating End Quantity:1Contact Position Arrangement Style:11 single mating endContact Removability:Nonremovable single mating end single contact groupingPolarization Method:Guide pin/socketShell Type:SolidEa-6b prowler aircraftOperating Tempurature Rating:Between -55.0 degrees celsius and 125.0 degrees celsiusTerminal Location:Back single mating end single contact groupingContact Surface Treatment:Gold single mating end single contact groupingContact Surface Treatment:Gold single mating end single contact groupingCurter Surface Treatment:Gold single mating end single contact groupingCurter Surface Treatment:Gold single mating end single contact groupingCurter Surface Treatment:Hexagon shape male post right-hand at 9 oclockIncluded Contact Quantity:11 single mating end single contact groupingCurted Up in single mating end single contact groupingCurted Contact Type:Round pin single mating end single contact groupingHexagon shape male post right-hand at 9 oclockIncluded Contact Type:Round pin single mating end single contact groupingCirclect Surface Treatment:Circlect Surface Treatment:Hexagon shape male post	Body Style:
0.870 inches Overall Height: 0.530 inches Overall Width: 0.340 inches Distance Between Mounting Facility Centers: 0.625 inches Mating End Quantity: 1 Contact Position Arrangement Style: 11 single mating end Contact Renovability: Nonremovable single mating end single contact grouping Polarization Method: Guide pin/socket Shell Type: Solid Ear-6b prowler aircraft Operating Tempurature Rating: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping Curicat Surface Treatment: Gold single mating end single contact grouping Hervinal Type: Solder well single mating end single contact grouping Guide Design And Location: Hexagon shape male post right-hand at 9 oclock Included Contact Type:	Straight shape
Overall Height:0.530 inchesOverall Width:0.340 inchesDistance Between Mounting Facility Centers:0.625 inchesMating End Quantity:1Contact Position Arrangement Style:11 single mating endContact Removability:Nonremovable single mating end single contact groupingPolarization Method:Guide pin/socketShell Type:SolidEa-6b prowler aircraftOperating Tempurature Rating:Between -55.0 degrees celsius and 125.0 degrees celsiusTerminal Location:Back single mating end single contact groupingContact Surface Treatment:Gold single mating end single contact groupingContact Surface Treatment:Gold single mating end single contact groupingCurtact Surface Treatment:Golder well single end single contact groupingCurtact Surface Treatment:Golder well single mating end single contact groupingCurtact Surface Treatment:Golder well single mating end single contact groupingCurtact Surface Treatment:Golder well single mating end single contact groupingCurtact Surface Treatment:Hexagon shape male post right-hand at 9 oclockIncluded Contact Type:Round pin single mating end single contact groupingCirtact Surface Treatment:Hexagon shape male post right-hand at 9 oclockIncluded Contact Type:Round pin single mating end single contact groupingCirtact Surface ToppingCirtact Surface Single cont	Overall Length:
0.530 inchesOverall Width:0.340 inchesDistance Between Mounting Facility Centers:0.625 inchesMating End Quantity:1Contact Position Arrangement Style:11 single mating endContact Removability:Nonremovable single mating end single contact groupingPolarization Method:Guide pin/socketShell Type:SolidEach prowler aircraftOperating Tempurature Rating:Between -55.0 degrees celsius and 125.0 degrees celsiusTerminal Location:Back single mating end single contact groupingContact Surface Treatment:Gold single mating end single contact groupingContact Surface Treatment:Gold single mating end single contact groupingCintact Surface Treatment:Golder well single end single contact groupingCintact Material:Solder well single mating end single contact groupingCintact Surface Treatment:Gold single mating end single contact groupingCintact Surface Treatment:Hexagon shape male post right-hand at 9 oclockIncluded Contact Quantity:11 single mating end single contact groupingCintact Quantity:11 single mating end single contact groupingCintact Quantity:11 single mating end single contact groupingCintact Quantity:12 single mating end single contact groupingCintact Surface Type:Round pin single mating end single contact groupingCintact Surface SingleCintact Surfac	0.870 inches
Overall Width:0.340 inchesDistance Between Mounting Facility Centers:0.625 inchesMating End Quantity:1Contact Position Arrangement Style:11 single mating endContact Removability:Nonremovable single mating end single contact groupingPolarization Method:Guide pin/socketShell Type:SolidEnd Application:Ea-6b prowler aircraftOperating Tempurature Rating:Between -55.0 degrees celsius and 125.0 degrees celsiusTerminal Location:Back single mating end single contact groupingContact Material:Copper alloy single mating end single contact groupingCurtact Surface Treatment:Gold single mating end single contact groupingCurtact Surface Treatment:Solder well single mating end single contact groupingHerninal Type:Solder well single mating end single contact groupingCurtact Surface Treatment:Gold single mating end single contact groupingHerninal Type:Solder well single mating end single contact groupingHucked Contact Quantity:11 single mating end single contact groupingHucked Contact Type:Round pin single mating end single contact groupingPortacted Contact Type:Round pin single mating end single contact groupingPortace Surface Treatment:Cortact Surface Type:Round pin single mating end single contact groupingPortace Surface Type:Round pin single mating end single contact g	Overall Height:
0.340 inches Distance Between Mounting Facility Centers: 0.625 inches Mating End Quantity: 1 Contact Position Arrangement Style: 11 single mating end Contact Removability: Nonremovable single mating end single contact grouping Polarization Method: Guide pin/socket Shell Type: Solid End Application: Ea-6b prowler aircraft Operating Tempurature Rating: Between -55.0 degrees celsius and 125.0 degrees celsius Terminal Location: Back single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping Curtact Surface Treatment: Gold single mating end single contact grouping Guide Design And Location: Hexagon shape male post right-hand at 9 oclock Included Contact Type: Round pin single mating end single contact grouping Included Contact Type: Round pin single mating end single contact grouping Included Contact Type:	0.530 inches
Distance Between Mounting Facility Centers: 0.625 inches Mating End Quantity: 1 Contact Position Arrangement Style: 11 single mating end Contact Removability: Nonremovable single mating end single contact grouping Polarization Method: Guide pin/socket Shell Type: Solid End Application: Ea-6b prowler aircraft Operating Tempurature Rating: Between -55.0 degrees celsius and 125.0 degrees celsius Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping Terminal Type: Solder well single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping Terminal Type: Solder well single mating end single contact grouping Hexagon shape male post right-hand at 9 oclock Included Contact Type: 11 single mating end single contact grouping Pacific Contact Type: Round pin single mating end single contact grouping Pacific Contact Type: Round pin single mating end single contact grouping Pacific Contact Type: Round pin single mating end single contact grouping Pacific Contact Surface Type: Round pin single mating end single contact grouping Pacific Contact Surface Sold	Overall Width:
0.625 inches Mating End Quantity: 1 Contact Position Arrangement Style: 11 single mating end Contact Removability: Nonremovable single mating end single contact grouping Polarization Method: Guide pin/socket Shell Type: Solid End Application: Ea-6b prowler aircraft Operating Tempurature Rating: Between -55.0 degrees celsius and 125.0 degrees celsius Terminal Location: Back single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping Terminal Type: Solder well single mating end single contact grouping Guide Design And Location: Haxagon shape male post right-hand at 9 oclock Included Contact Type: Round pin single mating end single contact grouping Ficuous Material And Location: Contact Surfaces gold	0.340 inches
Mating End Quantity: 1 Contact Position Arrangement Style: 11 single mating end Contact Removability: Nonremovable single mating end single contact grouping Polarization Method: Guide pin/socket Shell Type: Solid End Application: Ea-6b prowler aircraft Operating Tempurature Rating: Between -55.0 degrees celsius and 125.0 degrees celsius Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping Guide Design And Location: Hexagon shape male post right-hand at 9 oclock Included Contact Type: 11 single mating end single contact grouping Included Contact Type: Round pin single mating end single contact grouping Included Contact Type: Round pin single mating end single contact grouping Included Contact Type: Round pin single mat	Distance Between Mounting Facility Centers:
1 Contact Position Arrangement Style: 11 single mating end Contact Removability: Nonremovable single mating end single contact grouping Polarization Method: Guide pin/socket Shell Type: Solid End Application: Ea-8b prowler aircraft Operating Tempurature Rating: Between -55.0 degrees celsius and 125.0 degrees celsius Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Golds single mating end single contact grouping Contact Surface Treatment: Golds rowell single mating end single contact grouping Guide Design And Location: Hexagon shape male post right-hand at 9 oclock Included Contact Type: This single mating end single contact grouping Included Contact Type: Round pin single mating end single contact grouping Included Contact Type: Round pin single mating end single contact grouping Included Contact Type: Round pin single mating end single contact grouping <td>0.625 inches</td>	0.625 inches
Contact Position Arrangement Style: 11 single mating end Contact Removability: Nonremovable single mating end single contact grouping Polarization Method: Guide pin/socket Shell Type: Solid End Application: Ea-6b prowler aircraft Operating Tempurature Rating: Between -55.0 degrees celsius and 125.0 degrees celsius Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Golder well single mating end single contact grouping Guide Design And Location: Hexagon shape male post right-hand at 9 oclock Included Contact Quantity: 11 single mating end single contact grouping Miclude Contact Type: Round pin single mating end single contact grouping Included Contact Type: Round pin single mating end single contact grouping Precious Material And Location: Contact surfaces gold	Mating End Quantity:
11 single mating end Contact Removability: Nonremovable single mating end single contact grouping Polarization Method: Guide pin/socket Shell Type: Solid End Application: Ea-6b prowler aircraft Operating Tempurature Rating: Between -55.0 degrees celsius and 125.0 degrees celsius Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping Curtact Surface Treatment: Golds well single mating end single contact grouping Guide Design And Location: Hexagon shape male post right-hand at 9 oclock Included Contact Quantity: 11 single mating end single contact grouping Precious Material And Location: Contact surfaces gold	1
Contact Removability:Nonremovable single mating end single contact groupingPolarization Method:Guide pin/socketShell Type:SolidEnd Application:Ea-6b prowler aircraftOperating Tempurature Rating:Between -55.0 degrees celsius and 125.0 degrees celsiusTerminal Location:Back single mating end single contact groupingContact Material:Coper alloy single mating end single contact groupingContact Surface Treatment:Gold single mating end single contact groupingCurtact Surface Treatment:Golder well single mating end single contact groupingGuide Design And Location:Hexagon shape male post right-hand at 9 oclockIncluded Contact Type:11 single mating end single contact groupingPrecious Material And Location:Precious Material And Location:Contact surfaces gold	Contact Position Arrangement Style:
Nonremovable single mating end single contact grouping Polarization Method: Guide pin/socket Shell Type: Solid End Application: Ea-6b prowler aircraft Operating Tempurature Rating: Between -55.0 degrees celsius and 125.0 degrees celsius Terminal Location: Back single mating end single contact grouping Contact Material: Coper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping Contact Surface Treatment: Bolder well single mating end single contact grouping Guide Design And Location: Hexagon shape male post right-hand at 9 oclock Included Contact Type: Round pin single mating end single contact grouping Hexagon shape male post right-hand at 9 oclock Included Contact Type: Round pin single mating end single contact grouping Foreious Material And Location: Contact surfaces gold	11 single mating end
Polarization Method:Guide pin/socketShell Type:SolidEnd Application:Ea-6b prowler aircraftOperating Tempurature Rating:Between -55.0 degrees celsius and 125.0 degrees celsiusTerminal Location:Back single mating end single contact groupingContact Material:Copper alloy single mating end single contact groupingContact Surface Treatment:Gold single mating end single contact groupingTerminal Type:Solder well single mating end single contact groupingGuide Design And Location:Hexagon shape male post right-hand at 9 oclockIncluded Contact Type:11 single mating end single contact groupingPrecious Material And Location:Contact Surface Type:Round pin single mating end single contact grouping	Contact Removability:
Guide pin/socket Shell Type: Solid End Application: Ea-6b prowler aircraft Operating Tempurature Rating: Between -55.0 degrees celsius and 125.0 degrees celsius Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping Terminal Type: Solder well single mating end single contact grouping Guide Design And Location: Hexagon shape male post right-hand at 9 oclock Included Contact Type: 11 single mating end single contact grouping Precious Material And Location: Precious Material And Location: Contact surfaces gold	Nonremovable single mating end single contact grouping
Shell Type:SolidEnd Application:Ea-6b prowler aircraftOperating Tempurature Rating:Between -55.0 degrees celsius and 125.0 degrees celsiusTerminal Location:Back single mating end single contact groupingContact Material:Copper alloy single mating end single contact groupingContact Surface Treatment:Gold single mating end single contact groupingTerminal Type:Solder well single mating end single contact groupingGuide Design And Location:Hexagon shape male post right-hand at 9 oclockIncluded Contact Type:11 single mating end single contact groupingPrecious Material And Location:Round pin single mating end single contact groupingContact Surface Treatment:Contact Surface Operating end single contact groupingBuilder Design And Location:Precious Material And Location:Contact Surface Treating end single contact groupingContact Surface Sold	Polarization Method:
Solid End Application: Ea-6b prowler aircraft Operating Tempurature Rating: Between -55.0 degrees celsius and 125.0 degrees celsius Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping Terminal Type: Solder well single mating end single contact grouping Guide Design And Location: Hexagon shape male post right-hand at 9 oclock Included Contact Quantity: 11 single mating end single contact grouping Precious Material And Location: Contact surfaces gold	Guide pin/socket
End Application:Ea-6b prowler aircraftOperating Tempurature Rating:Between -55.0 degrees celsius and 125.0 degrees celsiusTerminal Location:Back single mating end single contact groupingContact Material:Copper alloy single mating end single contact groupingContact Surface Treatment:Gold single mating end single contact groupingTerminal Type:Solder well single mating end single contact groupingHexagon shape male post right-hand at 9 oclockIncluded Contact Quantity:11 single mating end single contact groupingPrecious Material And Location:Round pin single mating end single contact grouping	Shell Type:
Ea-6b prowler aircraft Operating Tempurature Rating: Between -55.0 degrees celsius and 125.0 degrees celsius Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping Terminal Type: Solder well single mating end single contact grouping Guide Design And Location: Hexagon shape male post right-hand at 9 oclock Included Contact Quantity: 11 single mating end single contact grouping Mexagon pingle mating end single contact grouping Contact Surface Treatment: Round pin single mating end single contact grouping Precious Material And Location: Contact surfaces gold	Solid
Operating Tempurature Rating:Between -55.0 degrees celsius and 125.0 degrees celsiusTerminal Location:Back single mating end single contact groupingContact Material:Copper alloy single mating end single contact groupingContact Surface Treatment:Gold single mating end single contact groupingTerminal Type:Solder well single mating end single contact groupingGuide Design And Location:Hexagon shape male post right-hand at 9 oclockIncluded Contact Type:11 single mating end single contact groupingPrecious Material And Location:Round pin single mating end single contact grouping	End Application:
Between -55.0 degrees celsius and 125.0 degrees celsiusTerminal Location:Back single mating end single contact groupingContact Material:Copper alloy single mating end single contact groupingContact Surface Treatment:Gold single mating end single contact groupingTerminal Type:Solder well single mating end single contact groupingGuide Design And Location:Hexagon shape male post right-hand at 9 oclockIncluded Contact Quantity:11 single mating end single contact groupingPrecious Material And Location:Contact surfaces gold	Ea-6b prowler aircraft
Terminal Location:Back single mating end single contact groupingContact Material:Copper alloy single mating end single contact groupingContact Surface Treatment:Gold single mating end single contact groupingTerminal Type:Solder well single mating end single contact groupingGuide Design And Location:Hexagon shape male post right-hand at 9 oclockIncluded Contact Quantity:11 single mating end single contact groupingPrecious Material And Location:Contact surfaces gold	Operating Tempurature Rating:
 Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping Terminal Type: Solder well single mating end single contact grouping Guide Design And Location: Hexagon shape male post right-hand at 9 oclock Included Contact Quantity: 11 single mating end single contact grouping Precious Material And Location: Contact surfaces gold 	Between -55.0 degrees celsius and 125.0 degrees celsius
Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping Terminal Type: Solder well single mating end single contact grouping Guide Design And Location: Hexagon shape male post right-hand at 9 oclock Included Contact Quantity: 11 single mating end single contact grouping Included Contact Type: Round pin single mating end single contact grouping Precious Material And Location: Contact surfaces gold	Terminal Location:
Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping Terminal Type: Solder well single mating end single contact grouping Guide Design And Location: Hexagon shape male post right-hand at 9 oclock Included Contact Quantity: 11 single mating end single contact grouping Included Contact Type: Round pin single mating end single contact grouping Precious Material And Location: Contact surfaces gold	Back single mating end single contact grouping
Contact Surface Treatment: Gold single mating end single contact grouping Terminal Type: Solder well single mating end single contact grouping Guide Design And Location: Hexagon shape male post right-hand at 9 oclock Included Contact Quantity: 11 single mating end single contact grouping Included Contact Type: Round pin single mating end single contact grouping Precious Material And Location: Contact surfaces gold	Contact Material:
Gold single mating end single contact grouping Terminal Type: Solder well single mating end single contact grouping Guide Design And Location: Hexagon shape male post right-hand at 9 oclock Included Contact Quantity: 11 single mating end single contact grouping Included Contact Type: Round pin single mating end single contact grouping Precious Material And Location: Contact surfaces gold	Copper alloy single mating end single contact grouping
Terminal Type:Solder well single mating end single contact groupingGuide Design And Location:Hexagon shape male post right-hand at 9 oclockIncluded Contact Quantity:11 single mating end single contact groupingIncluded Contact Type:Round pin single mating end single contact groupingPrecious Material And Location:Contact surfaces gold	Contact Surface Treatment:
Solder well single mating end single contact grouping Guide Design And Location: Hexagon shape male post right-hand at 9 oclock Included Contact Quantity: 11 single mating end single contact grouping Included Contact Type: Round pin single mating end single contact grouping Precious Material And Location: Contact surfaces gold	Gold single mating end single contact grouping
Guide Design And Location: Hexagon shape male post right-hand at 9 oclock Included Contact Quantity: 11 single mating end single contact grouping Included Contact Type: Round pin single mating end single contact grouping Precious Material And Location: Contact surfaces gold	Terminal Type:
Hexagon shape male post right-hand at 9 oclock Included Contact Quantity: 11 single mating end single contact grouping Included Contact Type: Round pin single mating end single contact grouping Precious Material And Location: Contact surfaces gold	Solder well single mating end single contact grouping
Included Contact Quantity: 11 single mating end single contact grouping Included Contact Type: Round pin single mating end single contact grouping Precious Material And Location: Contact surfaces gold	Guide Design And Location:
 11 single mating end single contact grouping Included Contact Type: Round pin single mating end single contact grouping Precious Material And Location: Contact surfaces gold 	Hexagon shape male post right-hand at 9 oclock
Included Contact Type: Round pin single mating end single contact grouping Precious Material And Location: Contact surfaces gold	Included Contact Quantity:
Round pin single mating end single contact grouping Precious Material And Location: Contact surfaces gold	11 single mating end single contact grouping
Precious Material And Location: Contact surfaces gold	Included Contact Type:
Contact surfaces gold	Round pin single mating end single contact grouping
-	Precious Material And Location:
Precious Material:	Contact surfaces gold
	Precious Material:
Gold	Gold



Special Test Features:

Dielectric coolant - polyaphaolefin or mil-c-87252 equivalent

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0