

View Online at <https://aerobasegroup.com/nsn/5935-01-496-3636>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape, external coupling

Environmental Protection:

Weatherproof

Cable Entrance Diameter:

0.437 inches

Distance From Mounting Shoulder To Front Face:

0.938 inches

Mounting Facility Thickness:

0.188 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

Tnc single mating end

Connector Locking Method:

Externally threaded shell

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 single mating end single contact grouping

Operating Temperature Rating:

Between -65.0 degrees fahrenheit and 260.0 degrees fahrenheit

Thready Qty Per Inch (tpi):

28

Thread Size:

0.438 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Beryllium single mating end single contact grouping and copper single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and tin single mating end single contact grouping

Shell Material:

Copper alloy

Shell Surface Treatment:

Silver

Included Contact Quantity:

1 single mating end single contact grouping

Bushing Accommodation Hole Shape:

Round w/flat

Included Contact Type:

Coaxial socket single mating end single contact grouping

Precious Material And Location:

Body plating silver and contact plating gold

Precious Material:

Silver and gold

Supplementary Features:

Mounting method - bushing

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0