## NSN 5935-01-497-0371

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-497-0371 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 32.5 millimeters **Overall Diameter:** 38.1 millimeters **Distance From Mounting Shoulder To Front Face:** 22.6 millimeters **Mounting Facility Thickness:** Between 1.6 millimeters and 3.2 millimeters **Threaded Device Type:** Back shell and coupling facility and mounting bushing **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 13-4 single mating end **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 and 105.0 and 140.0 and 204.0 and 307.0 Shell Type: Solid **Connector Locking Method:** Externally threaded shell **End Application:** 2350-01-420-4716 Thready Qty Per Inch (tpi): 10 **Thread Size:** 18.0 millimeters and 0.875 inches and 25.0 millimeters **Thread Pitch In Millimeters:** 1.00 **Terminal Location:** 

Back single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

NSN 5935-01-497-0371 Electrical Receptacle Connector - Page 2 of 2



Contact Surface Treatment:
Gold single mating end single contact grouping
nsert Material:
Plastic epoxy single mating end
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium
ncluded Contact Quantity:
4 single mating end single contact grouping
Bushing Accommodation Hole Shape:
Round w/flat
ncluded Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material:
Gold
Test Data Document:
31349-mil-dtl-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
31349-mil-dtl-38999/24 government specification
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Filg:
A039b0