Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-497-0371

Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Straight shape, external coupling
Overall Length:
32.5 millimeters
Overall Diameter:
38.1 millimeters
Distance From Mounting Shoulder To Front Face:
22.6 millimeters
Mounting Facility Thickness:
Between 1.6 millimeters and 3.2 millimeters
Threaded Device Type:
Back shell and coupling facility and mounting bushing
Mating End Quantity:
1
Contact Position Arrangement Style:
13-4 single mating end
Contact Removability:
Removable single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0 and 105.0 and 140.0 and 204.0 and 307.0
Shell Type:
Solid
Connector Locking Method:
Externally threaded shell
End Application:
2350-01-420-4716
Thready Qty Per Inch (tpi):
10
Thread Size:
18.0 millimeters and 0.875 inches and 25.0 millimeters
Thread Pitch In Millimeters:
1.00
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping



Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic epoxy single mating end

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium

Included Contact Quantity:

4 single mating end single contact grouping

Bushing Accommodation Hole Shape:

Round w/flat

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material:

Gold

Test Data Document:

81349-mil-dtl-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-dtl-38999/24 government specification

Shelf Life:

N/a

Unit Of Measure:

```
---
```

Demilitarization:

No

Fiig:

A039b0