NSN 5935-01-497-1503



Electrical Plug Connector - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5935-01-497-1503 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, internal coupling **Overall Length:** 1.500 inches **Overall Diameter:** 1.156 inches **Environmental Protection:** Moisture proof and salt water resistant and fuel resistant and oil resistant **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Position Arrangement Style:** 14s-5 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 200.0 single mating end single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 250.0 single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: Potting **Connector Cable Strain Relief Method:** Potting type **Features Provided:** Safety wire hole Thready Qty Per Inch (tpi): 20 **Thread Size:** 0.875 inches

Terminal Location:Back single mating end

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

NSN 5935-01-497-1503

Electrical Plug Connector - Page 2 of 2



contact grouping

Contact Surface Treatment:
Silver single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Contact Surface Treatment Specification:
Qq-s-265 federal specification single treatment response single mating end single
Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Metal
Shell Surface Treatment:
Cadmium
Shell Surface Treatment Specification:
Qq-p-416, type 2, cl 3 federal specification single treatment response
Insert Material Specification:
Mil-m-14 military specification single material response single mating end
Included Contact Quantity:
5 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material:
Gold
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A039b0

Mil-m-14 spec.

Mil-std (military Standard):