## NSN 5935-01-497-6400

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-497-6400

Body Style:
Straight type
Overall Length:
3.760 inches
Overall Height:
1.416 inches
Overall Width:
0.360 inches
Environmental Protection:
Corrosion resistant and fungus resistant and humidity resistant and shock resistant and vibration proof
Unthreaded Mounting Hole Diameter:
0.116 inches
Distance Between Mounting Facility Centers:
3.600 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
2 rows of contacts non-inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Polarization Method:
Mating end
Connector Locking Method:
Latch
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Contact Surface Treatment Specification:
Mil-g-45204, type 2, grade c, class 1 military specification single treatment response single mating end single contact grouping
Terminal Type:
Pin single mating end single contact grouping
Contact Material Specification:

Qq-c-530 federal specification single material response single mating end single contact grouping or qq-b-750 federal specification single material response single response single single single response single response si

## Included Contact Quantity:

single contact grouping

60 single mating end single contact grouping

## **Included Contact Type:**

Round pin single mating end single contact grouping

## NSN 5935-01-497-6400

Electrical Receptacle Connector - Page 2 of 2



Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.060 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0

Mil-std (military Standard):

Mil-g-45204 spec.