

View Online at <https://aerobasegroup.com/nsn/5935-01-497-6644>

Body Style:

Straight shape

Overall Length:

3.600 inches

Overall Height:

0.730 inches

Overall Width:

0.520 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

1 row of contacts non-inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

1.0 single mating end single contact grouping

Connector Locking Method:

Friction

End Application:

Cass, usm-66 electrical equipment test system

Operating Temperature Rating:

Between -65.0 degrees celsius and 200.0 degrees celsius

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic polyester glass filled single mating end

Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response single mating end single contact grouping

Criticality Code Justification:

Agav

Terminal Type:

Printed circuit single mating end single contact grouping

Included Contact Quantity:

72 single mating end single contact grouping

Included Contact Type:

Square pin single mating end single contact grouping

Product Name:

Assembly, .025 square post terminal strip

Special Features:

USED-ON-INT-ERFA

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.072 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.