

View Online at <https://aerobasegroup.com/nsn/5935-01-497-6645>

**Body Style:**

Straight shape

**Overall Length:**

4.000 inches

**Overall Height:**

0.730 inches

**Overall Width:**

0.520 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

1 row of contacts non-inserted board single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

1.0 single mating end single contact grouping

**Connector Locking Method:**

Friction

**End Application:**

Cass, usm-66 electrical equipment test system

**Operating Temperature Rating:**

Between -65.0 degrees celsius and 200.0 degrees celsius

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping

**Insert Material:**

Plastic polyester glass filled single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204 military specification single treatment response single mating end single contact grouping

**Criticality Code Justification:**

Agav

**Terminal Type:**

Printed circuit single mating end single contact grouping

**Included Contact Quantity:**

40 single mating end single contact grouping

**Included Contact Type:**

Square pin single mating end single contact grouping

**Product Name:**

Assembly, .025 square post terminal strip

**Special Features:**

USED-ON-INT-ERFA

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.040 gold grains, troy

**Precious Material:**

Gold

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.