NSN 5935-01-498-4322

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-498-4322

Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Straight shape, internal coupling
Overall Length:
0.826 inches
Overall Diameter:
0.750 inches
Environmental Protection:
Corrosion resistant and weather resistant and vibration resistant and shock resistant
Threaded Device Type:
Back shell
Mating End Quantity:
1
Contact Position Arrangement Style:
Adem 8-98 single mating end
Contact Removability:
Removable single mating end single contact grouping
Polarization Method:
Key or multiple key
Insert Position In Deg:
100.0 and 128.0 and 228.0 and 265.0 and 340.0
Shell Type:
Solid
Connector Locking Method:
Bayonet slot
End Application:
M3p rev-m; radar threat emiter an/mst-t1
Thread Size:
0.687 inches
Terminal Location:
Back single mating end single contact grouping
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium

Shell Surface Treatment Specification:Qq-p-416 federal specification all treatment responses

NSN 5935-01-498-4322

Mil-dtl-38999 spec.

Electrical Plug Connector - Page 2 of 2



Included Contact Quantity:
3 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Special Features:
Contacts per mil-c-39029/57-357
Color:
Olive drab
Precious Material And Location:
Contact surfaces gold
Precious Material:
Gold
Test Data Document:
81349-mil-dtl-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Unef
Specification Data:
96906-ms27473 government standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):