## NSN 5935-01-498-4650

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-498-4650

·
Body Style:
Straight shape, external coupling
Overall Length:
1.937 inches
Overall Height:
2.250 inches
Overall Width:
2.250 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
1.750 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
1.750 inches
Distance From Mounting Shoulder To Front Face:
0.875 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
32-17 single mating end
Contact Removability:
Removable single mating end single contact grouping
Polarization Method:
Key, multiple key groove
Insert Position In Deg:
250.0
Shell Type:
Solid
End Application:
Interlock assembly; seawolf class ssn
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and nickel single mating end single contact grouping
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum
Shell Surface Treatment:
Cadmium and chromate and nickel

Included Contact Quantity:

4 single mating end single contact grouping

## NSN 5935-01-498-4650

Electrical Receptacle Connector - Page 2 of 2



Round pin single mating end single contact grouping	
Precious Material And Location:	
Contact surfaces gold	
Precious Material:	
Gold	

**Test Data Document:** 

**Included Contact Type:** 

81349-mil-c-5015 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Specification Data:** 

96906-ms3402 government standard

Shelf Life:

N/a

**Unit Of Measure:** 

\_

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-c-5015 spec.