NSN 5935-01-498-8409

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-498-8409 **Thread Class:** 2a and 2b **Thread Direction:** Right-hand and right-hand **Body Style:** Straight shape, internal coupling **Overall Length:** 1.370 inches **Overall Diameter:** 0.997 inches **Environmental Protection:** Corrosion resistant and fungus resistant and salt water resistant and shock resistant and vibration resistant and weather resistant **Threaded Device Type:** Back shell and coupling facility **Mating End Quantity: Contact Position Arrangement Style:** Agac 10-6 single mating end **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Key or multiple key **Insert Position In Deg:** 0.0 and 102.0 and 132.0 and 248.0 and 320.0 Shell Type: Solid **Connector Locking Method:** Internally threaded coupling nut Thready Qty Per Inch (tpi): 24 and 24 **Thread Size:** 0.625 inches and 0.688 inches **Terminal Location:** Back single mating end single contact grouping **Terminal Type:** Crimp single mating end single contact grouping

Shell Material:

Aluminum

Shell Surface Treatment:

Cadmium

Shell Surface Treatment Specification:

Qq-p-416 federal specification all treatment responses

NSN 5935-01-498-8409

Mil-dtl-83723 spec.

Electrical Plug Connector - Page 2 of 2



Included Contact Quantity:
6 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Special Features:
Contacts per mil-c-39029/4-110
Color:
Olive drab
Precious Material And Location:
Contact surfaces gold
Precious Material:
Gold
Test Data Document:
81349-mil-dtl-83723 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Unef and unef
Specification Data:
81349-mil-dtl-83723 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):