NSN 5935-01-498-8890

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-498-8890 **Thread Class:** 2b **Thread Direction:** Right-hand **Body Style:** Rectangular shape, angle **Overall Length:** Between 2.073 inches and 2.103 inches **Overall Height:** Between 0.479 inches and 0.509 inches **Overall Width:** 0.716 inches **Environmental Protection:** Moisture resistant and corrosion resistant and vibration resistant and shock resistant **Distance Between Mounting Facility Centers:** Between 1.847 inches and 1.857 inches **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 25 single mating end **Contact Maximum Current Rating In Amps:** 5.0 single mating end single contact grouping **Polarization Method:** Mating end **Connector Locking Method:** Internally threaded coupling nut **Operating Tempurature Rating:** Between -65.0 degrees celsius and 150.0 degrees celsius Thready Qty Per Inch (tpi): 40 **Thread Size:** 0.112 inches **Terminal Location:** Side single mating end all contact groupings **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and copper single mating end single contact grouping or nickel single mating end single contact grouping **Insert Material:** Plastic polyester glass filled single mating end or plastic polyester single mating end

Pin single mating end all contact groupings

Terminal Type:

NSN 5935-01-498-8890 Electrical Receptacle Connector - Page 2 of 2



Shell Material:	
Steel	
Shell Surface Treatment:	
Chromate and cadmium	
Included Contact Quantity:	
25 single mating end single contact grouping	
Included Contact Type:	
Round socket single mating end single contact grouping	
Precious Material And Location:	
Contact plating gold	
Precious Material:	
Gold	
Supplementary Features:	
Mounting method - unthreaded hole	
Thread Series Designator:	
Unc	
Shelf Life:	
N/a	
Unit Of Measure:	
. -	
Demilitarization:	
No	
Fiig:	
A039b0	