Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-498-8931

Thread Class:
2b
Thread Direction:
Right-hand
Body Style:
Rectangular shape, angle
Overall Length:
Between 1.526 inches and 1.556 inches
Overall Height:
Between 0.479 inches and 0.509 inches
Overall Width:
0.711 inches
Environmental Protection:
Moisture resistant and corrosion resistant and vibration resistant and shock resistant
Distance Between Mounting Facility Centers:
Between 1.307 inches and 1.317 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
15 single mating end
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Polarization Method:
Mating end
Connector Locking Method:
Internally threaded coupling nut
Operating Tempurature Rating:
Between -65.0 degrees celsius and 150.0 degrees celsius
Thready Qty Per Inch (tpi):
40
Thread Size:
0.112 inches
Terminal Location:
Side single mating end all contact groupings
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and copper single mating end single contact grouping or nickel single mating end single
contact grouping
Insert Material:
Plastic polyester glass filled single mating end or plastic polyester single mating end
Terminal Type:
Pin single mating end all contact groupings



Shell Material:

Steel

Shell Surface Treatment:

Chromate and zinc

Included Contact Quantity:

15 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact plating gold

Precious Material:

Gold

Supplementary Features:

Mounting method - unthreaded hole

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

--

Fiig:

A039b0