Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-498-9229

# Thread Class:

2a and 2b

# **Thread Direction:**

Right-hand and right-hand

# Body Style:

Straight shape, internal coupling

### **Overall Length:**

1.370 inches

## **Overall Diameter:**

1.499 inches

## **Environmental Protection:**

Corrosion resistant and fungus resistant and salt water resistant and shock resistant and vibration resistant and weather resistant

## **Threaded Device Type:**

Back shell and coupling facility

## Mating End Quantity:

1

## Contact Position Arrangement Style:

Bhba 18-31 single mating end

## **Contact Removability:**

Removable single mating end single contact grouping

## Polarization Method:

Key or multiple key

## **Insert Position In Deg:**

0.0 and 18.0 and 149.0 and 192.0 and 259.0

## Shell Type:

Solid

## **Connector Locking Method:**

Internally threaded coupling nut

## Thready Qty Per Inch (tpi):

18 and 18

# Thread Size:

1.062 inches and 1.188 inches

## **Terminal Location:**

Back single mating end single contact grouping

## **Terminal Type:**

Crimp single mating end single contact grouping

## Shell Material:

Aluminum

# Shell Surface Treatment:

Cadmium

## Shell Surface Treatment Specification:

Qq-p-416 federal specification all treatment responses

# NSN 5935-01-498-9229

Electrical Plug Connector - Page 2 of 2



#### **Included Contact Quantity:**

31 single mating end single contact grouping

## Included Contact Type:

Round pin single mating end single contact grouping

#### **Special Features:**

Contacts per mil-c-39029/4-110

Color:

Olive drab

**Precious Material And Location:** 

Contact surfaces gold

### **Precious Material:**

Gold

#### **Test Data Document:**

81349-mil-dtl-83723 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

### **Thread Series Designator:**

Unef and unef

#### **Specification Data:**

81349-mil-dtl-83723 government specification

Shelf Life:

N/a

#### Unit Of Measure:

--

## **Demilitarization:**

No

#### Fiig:

A039b0

## Mil-std (military Standard):

Mil-dtl-83723 spec.