## NSN 5935-01-498-9233

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-498-9233

Thread Class:

Till Caa Olass

2a and 2b

**Thread Direction:** 

Right-hand and right-hand

**Body Style:** 

Straight shape, internal coupling

**Overall Length:** 

1.370 inches

**Overall Diameter:** 

1.499 inches

**Environmental Protection:** 

Corrosion resistant and fungus resistant and salt water resistant and shock resistant and vibration resistant and weather resistant

**Threaded Device Type:** 

Back shell and coupling facility

**Mating End Quantity:** 

1

**Contact Position Arrangement Style:** 

36-9 single mating end

**Contact Removability:** 

Removable single mating end single contact grouping

**Polarization Method:** 

Key or multiple key

**Insert Position In Deg:** 

0.0 and 92.0 and 152.0 and 222.0 and 342.0

Shell Type:

Solid

**Connector Locking Method:** 

Internally threaded coupling nut

Thready Qty Per Inch (tpi):

18 and 18

**Thread Size:** 

1.062 inches and 1.188 inches

**Terminal Location:** 

Back single mating end single contact grouping

**Terminal Type:** 

Crimp single mating end single contact grouping

**Shell Material:** 

Aluminum

**Shell Surface Treatment:** 

Cadmium

**Shell Surface Treatment Specification:** 

Qq-p-416 federal specification all treatment responses

## NSN 5935-01-498-9233

Mil-dtl-83723 spec.

Electrical Plug Connector - Page 2 of 2



Included Contact Quantity:
31 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Special Features:
Contacts per mil-c-39029/4-110
Color:
Olive drab
Precious Material And Location:
Contact surfaces gold
Precious Material:
Gold
Test Data Document:
81349-mil-dtl-83723 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Unef and unef
Specification Data:
81349-mil-dtl-83723 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):