

View Online at <https://aerobasegroup.com/nsn/5935-01-498-9664>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape, external coupling

Overall Length:

2.001 inches

Environmental Protection:

Dust resistant and sand resistant and pressure proof and vibration resistant and fungus resistant and salt water resistant and corrosion resistant and humidity resistant and explosion proof

Mating End Quantity:

2

Contact Position Arrangement Style:

Tnc 2nd mating end

Connector Locking Method:

Externally threaded shell and friction

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 all mating ends all contact groupings

Operating Temperature Rating:

Between -54.0 degrees celsius and 85.0 degrees celsius

Thready Qty Per Inch (tpi):

24

Thread Size:

0.625 inches

Contact Material:

Beryllium and copper all mating ends all contact groupings

Contact Surface Treatment:

Gold and nickel and copper all mating ends all contact groupings

Shell Material:

Stainless steel and copper alloy

Shell Surface Treatment:

Passivate and nickel

Included Contact Quantity:

1 all mating ends all contact groupings

Included Contact Type:

Coaxial socket all mating ends all contact groupings

Precious Material And Location:

Contact plating gold

Precious Material:

Gold

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0