## NSN 5935-01-499-7223

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-499-7223

**Body Style:** 

Straight shape, flange mount external coupling

**Overall Length:** 

1.046 inches

**Overall Height:** 

1.582 inches

**Overall Width:** 

1.582 inches

**Unthreaded Mounting Hole Diameter:** 

Between 0.123 inches and 0.138 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

1.250 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.250 inches

**Mating End Quantity:** 

1

**Contact Position Arrangement Style:** 

21-11 single mating end

**Polarization Method:** 

Keyway or multiple keyway

**Insert Position In Deg:** 

135.0 and 170.0 and 200.0 and 310.0

**Connector Locking Method:** 

Bayonet pin

**Operating Tempurature Rating:** 

Between -65.0 degrees celsius and 200.0 degrees celsius

**Terminal Location:** 

Back single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping

**Terminal Type:** 

Crimp single mating end single contact grouping

**Shell Material:** 

Stainless steel

**Shell Surface Treatment:** 

**Passivate** 

**Included Contact Quantity:** 

11 single mating end single contact grouping

**Included Contact Type:** 

Round socket single mating end single contact grouping

**Special Features:** 

3 bayonet posts, 120 degrees from each other, the first being at 6 oclock position.

## NSN 5935-01-499-7223

Electrical Receptacle Connector - Page 2 of 2



Precious Material And Location:
Contact plating gold
Precious Material:
Gold
Supplementary Features:
Mounting method - unthreaded hole
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):

Mil-dtl-38999 spec.