

View Online at <https://aerobasegroup.com/nsn/5935-01-499-9253>

Thread Class:

2a

Thread Direction:

Right-hand

Environmental Protection:

Corrosion resistant and fuel resistant

Unthreaded Mounting Hole Diameter:

0.782 inches

Cable Entrance Diameter:

0.666 inches

Threaded Device Type:

Coupling facility

Contact Removability:

Removable single mating end all contact groupings

Contact Maximum Ac Voltage Rating In Volts:

600.0 single mating end all contact groupings

Contact Maximum Dc Voltage Rating In Volts:

850.0 single mating end all contact groupings

Connector Locking Method:

Externally threaded coupling nut

Connector Cable Strain Relief Method:

Crimp type

End Application:

Patrol aircraft

Thread Length:

0.219 inches

Operating Temperature Rating:

Between 65.0 degrees celsius and 175.0 degrees celsius

Thread Size:

0.812 inches

Terminal Location:

Front single mating end all contact groupings

Terminal Type:

Crimp single mating end all contact groupings

Shell Material:

Nickel

Shell Surface Treatment:

Cadmium

Bushing Accommodation Hole Shape:

Round

Special Features:

Bayonet coupling, crimp removable, rear release, scoop-proof

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0