Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-500-0635

Thread Direction:
Right-hand
Body Style:
Straight shape, external coupling
Overall Length:
32.0 millimeters
Overall Height:
Between 42.3 millimeters and 43.4 millimeters
Overall Width:
Between 42.3 millimeters and 43.4 millimeters
Unthreaded Mounting Hole Diameter:
4.0 millimeters
Center To Center Distance Between Mounting Facilities Parallel To Height:
35.0 millimeters
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
35.0 millimeters
Distance From Mounting Shoulder To Front Face:
19.2 millimeters
Threaded Device Type:
Back shell
Mating End Quantity:
1
Contact Position Arrangement Style:
23-53 single mating end
Contact Removability:
Removable single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Detent
Thread Size:
34.0 millimeters
Thread Pitch In Millimeters:
1.00
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Copper and single maning end single contact grouping



#### **Contact Surface Treatment:**

Gold single mating end single contact grouping

#### **Terminal Type:**

Crimp single mating end single contact grouping

#### Shell Material:

Aluminum alloy

## Shell Surface Treatment:

Nickel

#### **Thread Tolerance Class:**

6g external

#### **Included Contact Quantity:**

53 single mating end single contact grouping

#### **Included Contact Type:**

Round pin single mating end single contact grouping

#### **Precious Material And Location:**

Contact surfaces gold

**Precious Material:** 

Gold

#### **Test Data Document:**

81349-mil-c38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

environmental and performance requirements and test conditions that a

# Thread Series Designator:

lso m

# Specification Data:

81349-mil-c-38999/40 government specification

### Shelf Life:

N/a

#### Unit Of Measure:

---

#### Demilitarization:

No

```
Fiig:
```

A039b0