## NSN 5935-01-500-1159

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-500-1159

**Body Style:** 

Straight shape, external coupling

**Overall Length:** 

0.697 inches

**Overall Height:** 

1.328 inches

**Overall Width:** 

1.328 inches

**Environmental Protection:** 

Moisture proof and salt water resistant and vibration proof

**Unthreaded Mounting Hole Diameter:** 

Between 0.115 inches and 0.130 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

1.062 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.062 inches

**Distance From Mounting Shoulder To Front Face:** 

Between 0.442 inches and 0.447 inches

**Mating End Quantity:** 

1

**Contact Position Arrangement Style:** 

18-28 single mating end

**Contact Removability:** 

Removable single mating end all contact groupings

**Polarization Method:** 

Keyway or multiple keyway

**Insert Position In Deg:** 

0.0 and 95.0 and 132.0 and 232.0 and 260.0 and 342.0

Shell Type:

Solid

**Connector Locking Method:** 

Bayonet pin

**Terminal Location:** 

Back single mating end all contact groupings

**Contact Material:** 

Copper alloy single mating end all contact groupings

**Contact Surface Treatment:** 

Gold single mating end all contact groupings and silver single mating end all contact groupings

**Terminal Type:** 

Crimp single mating end all contact groupings

**Shell Material:** 

Aluminum alloy

## NSN 5935-01-500-1159

Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment:
Nickel
Included Contact Quantity:
26 single mating end 2nd contact grouping
Included Contact Type:
Round pin single mating end all contact groupings
Precious Material:
Gold and silver
Test Data Document:
81349-mil-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
96906-ms27508 government standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-c-38999 spec.