Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-500-1168

### **Body Style:**

Straight shape, external coupling

# **Overall Length:**

0.697 inches

# **Overall Height:**

1.328 inches

# **Overall Width:**

1.328 inches

#### **Environmental Protection:**

Moisture proof and salt water resistant and vibration proof

#### **Unthreaded Mounting Hole Diameter:**

Between 0.115 inches and 0.130 inches

# Center To Center Distance Between Mounting Facilities Parallel To Height:

1.062 inches

#### Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.062 inches

# Distance From Mounting Shoulder To Front Face:

Between 0.442 inches and 0.447 inches

# Mating End Quantity:

1

#### **Contact Position Arrangement Style:**

18-28 single mating end

#### **Contact Removability:**

Removable single mating end all contact groupings

#### **Polarization Method:**

Keyway or multiple keyway

#### **Insert Position In Deg:**

0.0

### Shell Type:

Solid

# **Connector Locking Method:**

Bayonet pin

#### **Terminal Location:**

Back single mating end all contact groupings

#### **Contact Material:**

Copper alloy single mating end all contact groupings

# **Contact Surface Treatment:**

Gold single mating end all contact groupings and silver single mating end all contact groupings

# **Terminal Type:**

Crimp single mating end all contact groupings

# Shell Material:

Aluminum alloy

Electrical Receptacle Connector - Page 2 of 2



# Shell Surface Treatment:

Nickel

Included Contact Quantity:

26 single mating end 2nd contact grouping

Included Contact Type:

Round socket single mating end all contact groupings

# Precious Material:

Gold and silver

### **Test Data Document:**

81349-mil-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

#### **Specification Data:**

96906-ms27508 government standard

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-c-38999 spec.