NSN 5935-01-501-4768

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-501-4768 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape **Overall Length:** 1.090 inches **Overall Width:** 0.535 inches **Threaded Device Type:** Coupling facility **Mating End Quantity: End Application:** Anti-submarine aircraft Thready Qty Per Inch (tpi): 24 **Thread Size:** 0.625 inches **Contact Material:** Copper alloy single mating end all contact groupings **Contact Surface Treatment:** Gold single mating end all contact groupings **Contact Surface Treatment Specification:** Mil-g-45204 military specification single treatment response single mating end all contact groupings **Criticality Code Justification:** Agav **Terminal Type:** Screw w/wire lock single mating end all contact groupings **Contact Material Specification:** Qq-c-530 military specification single material response single mating end all contact groupings **Shell Material:** Stainless steel **Shell Surface Treatment: Passivate**

Shell Surface Treatment Specification:

Qq-p-35 military specification single treatment response

Shell Material Specification:

Astma582 assn standard single material response

Product Name:

Replaceable front end 'n' female bulkhead

NSN 5935-01-501-4768

Electrical Receptacle Connector - Page 2 of 2



S	pe	cia	al F	-ea	ıtu	re	S
---	----	-----	------	-----	-----	----	---

Dielectrics are made of polytetrafluoroethylene, astm d1457; jam nut is made of stainless steel, astm a582 with passivated surface treatment, qq-p-35

Precious Material And Location:

Contacts gold

Precious Material:

Gold

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A039b0

Mil-std (military Standard):

spec.