NSN 5935-01-503-1105

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-503-1105

Thread Class: 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** Between 1.681 inches and 1.686 inches **Overall Height:** Between 1.802 inches and 1.822 inches **Overall Width:** Between 1.802 inches and 1.822 inches **Unable To Decode:** Unable to decode and unable to decode **Unable To Decode:** Unable to decode and unable to decode **Environmental Protection:** Corrosion resistant and moisture resistant and shock resistant and vibration resistant Center To Center Distance Between Mounting Facilities Parallel To Height: Between 1.375 inches and 1.500 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 1.375 inches and 1.500 inches **Distance From Mounting Shoulder To Front Face:** Between 0.785 inches and 0.790 inches **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 25-35 single mating end **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 80.0 and 142.0 and 196.0 and 293.0 **Connector Locking Method:** Externally threaded shell **End Application:** Cec provision, hawkeye e-2c aircraft **Operating Tempurature Rating:** Between -55.0 degrees celsius and 125.0 degrees celsius

Features Provided:

Emi filter

Thread Size:

1.625 inches

NSN 5935-01-503-1105

Electrical Receptacle Connector - Page 2 of 2



Terminal Location:
Back single mating end single contact grouping
Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium
Included Contact Quantity:
128 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Special Features:
500 salt spray resistant
Color:
Olive drab
Supplementary Features:
Mounting method - slot
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0