Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-504-4367

## Body Style:

Straight shape, external coupling

### **Overall Length:**

31.5 millimeters

# **Overall Height:**

Between 30.7 millimeters and 31.3 millimeters

#### **Overall Width:**

Between 30.7 millimeters and 31.3 millimeters

### **Environmental Protection:**

Corrosion resistant

## Center To Center Distance Between Mounting Facilities Parallel To Height:

#### 24.61 millimeters

## Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

24.61 millimeters

### **Distance From Mounting Shoulder To Front Face:**

Between 19.5 millimeters and 20.9 millimeters

### Mating End Quantity:

1

### **Contact Position Arrangement Style:**

15-19 single mating end

## Contact Removability:

Removable single mating end single contact grouping

#### **Polarization Method:**

Key, multiple key groove

#### **Insert Position In Deg:**

0.0 and 108.0 and 165.0 and 215.0 and 270.0

#### Shell Type:

Solid

#### **Terminal Location:**

Back single mating end single contact grouping

#### **Contact Material:**

Copper alloy single mating end single contact grouping

#### **Contact Surface Treatment:**

Gold single mating end single contact grouping

#### **Terminal Type:**

Crimp single mating end single contact grouping

## Shell Material:

Plastic epoxy and resin synthetic

#### **Included Contact Quantity:**

19 single mating end single contact grouping

#### **Included Contact Type:**

Round socket single mating end single contact grouping



Special Features:

Emi shielding

Precious Material And Location:

Contact surfaces gold

Precious Material:

Gold

Test Data Document:

81349-mil-dtl-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

#### **Specification Data:**

81349-mil-dtl-38999/20 government specification

**Shelf Life:** N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A039b0