NSN 5935-01-505-0126

11 single mating end single contact grouping

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-505-0126

| Thread Class: |
|--|
| 2b |
| Thread Direction: |
| Right-hand and right-hand |
| Body Style: |
| Straight shape, internal coupling |
| Overall Length: |
| 33.16 millimeters |
| Overall Diameter: |
| 37.3 millimeters |
| Environmental Protection: |
| Corrosion resistant and salt spray proof and shock resistant and vibration resistant and weather resistant |
| Threaded Device Type: |
| Back shell and coupling facility |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| Zaaa 19-11 single mating end |
| Contact Removability: |
| Removable single mating end single contact grouping |
| Polarization Method: |
| Key or multiple key |
| Insert Position In Deg: |
| 0.0 and 80.0 and 142.0 and 196.0 and 293.0 |
| Shell Type: |
| Solid |
| Connector Locking Method: |
| Internally threaded coupling ring |
| Thread Size: |
| 28.0 millimeters and 1.250 inches |
| Terminal Location: |
| Back single mating end single contact grouping |
| Terminal Type: |
| Crimp single mating end single contact grouping |
| Shell Material: |
| Plastic |
| Shell Surface Treatment: |
| Nickel |
| Thread Tolerance Class: |
| 6g external |
| Included Contact Quantity: |

NSN 5935-01-505-0126

Electrical Plug Connector - Page 2 of 2



| Included Contact Type: |
|--|
| Round socket single mating end single contact grouping |
| Special Features: |
| CONT-AC-TSP-ERMI |
| Precious Material And Location: |
| Contact surfaces gold |
| Precious Material: |
| Gold |
| Thread Series Designator: |
| Iso m and special acme |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A039b0 |

Mil-std (military Standard):

Mil-dtl-38999 spec.