NSN 5935-01-506-6809

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-506-6809 **Thread Class:** 2a **Thread Direction:** Left-hand **Body Style:** Straight shape, external coupling **Unable To Decode:** Unable to decode and unable to decode **Overall Length:** 1.625 inches **Overall Height:** 1.738 inches **Overall Width:** 1.738 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 1.281 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.281 inches **Distance From Mounting Shoulder To Front Face:** 0.898 inches **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Position Arrangement Style:** 23-64 single mating end **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 and 67.0 and 164.0 and 218.0 and 280.0 Shell Type: Solid **Connector Locking Method:** Externally threaded shell Thready Qty Per Inch (tpi): 10 **Thread Size:** 1.500 inches

Terminal Location:

Back single mating end single contact grouping

NSN 5935-01-506-6809

Electrical Receptacle Connector - Page 2 of 2



Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum
Shell Surface Treatment:
Cadmium
Included Contact Quantity:
64 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Special Features:
Contacts per mil-c-39029/83-508
Color:
Olive drab
Precious Material And Location:
Contact surfaces gold
Precious Material:
Gold
Test Data Document:
81349-mil-c-28840 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Double stub
Specification Data:
81349-mil-c-28840/12 government specification
Shelf Life:
N/a
Unit Of Measure:
.
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-c-28840 spec.