## NSN 5935-01-506-8588

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-506-8588

Thread Class:
2a and 2b
Thread Direction:
Right-hand and right-hand
Body Style:
Straight shape, internal coupling
Overall Length:
2.125 inches
Overall Diameter:
1.969 inches
Environmental Protection:
Corrosion resistant and salt spray proof and shock resistant and vibration resistant and weather resistant
Threaded Device Type:
Back shell and coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
28-11 single mating end
Contact Removability:
Removable single mating end all contact groupings
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
250.0
Shell Type:
Solid
Connector Locking Method:
Internally threaded coupling ring
Thready Qty Per Inch (tpi):
18 and 18
Thread Size:
1.750 inches and 1.750 inches
Terminal Location:
Back single mating end all contact groupings
Terminal Type:
Crimp single mating end all contact groupings
Shell Material:
Stainless steel
Shell Surface Treatment:
Cadmium

Included Contact Quantity:

4 single mating end 1st contact grouping

## NSN 5935-01-506-8588

Electrical Plug Connector - Page 2 of 2



Included Contact Type:
Round socket single mating end all contact groupings
Special Features:
Contacts per mil-c-39029/45-295 and mil-c-39029/45-297
Color:
Black
Precious Material And Location:
Contact size 16 gold and contact size 12 silver
Precious Material:
Gold and silver
Test Data Document:
81349-mil-dtl-5015 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Uns and uns
Specification Data:
96906-ms3406 government standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
Accord

A039b0

Mil-std (military Standard):

Mil-dtl-5015 spec.