NSN 5935-01-507-3028

Thread Class: 2a and 2b

Thread Direction:

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-507-3028

Right-hand and right-hand
Body Style:
Straight shape, internal coupling w/strain relief
Body Length:
2.438 inches
Overall Diameter:
1.263 inches
Cable Entrance Diameter:
Between 0.250 inches and 0.416 inches
Threaded Device Type:
Back shell and coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
15-21 single mating end
Contact Removability:
Removable single mating end single contact grouping
Polarization Method:
Key or multiple key
Insert Position In Deg:
0.0 and 80.0 and 142.0 and 196.0 and 293.0
Shell Type:
Split
Connector Locking Method:
Internally threaded coupling ring
Connector Cable Strain Relief Method:
Cable clamp
Thready Qty Per Inch (tpi):
20 and 10
Thread Size:
1.000 inches and 1.062 inches
Terminal Location:
Back single mating end single contact grouping
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum
Shell Surface Treatment:
Cadmium

NSN 5935-01-507-3028Electrical Plug Connector - Page 2 of 2

A039b0



Included Contact Quantity:
21 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Special Features:
Contacts per mil-c-39029/84-509
Color:
Olive drab
Precious Material And Location:
Contact surfaces gold
Precious Material:
Gold
Test Data Document:
81349-mil-c-28840 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Unef and double stub
Specification Data:
81349-mil-c-28840/17 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: