

View Online at <https://aerobasegroup.com/nsn/5935-01-507-3181>

Body Style:

Straight shape w/screw locks

Environmental Protection:

Shock resistant and vibration resistant and salt spray proof

Mating End Quantity:

1

Contact Position Arrangement Style:

15 single mating end

Contact Maximum Current Rating In Amps:

3.0 single mating end single contact grouping

Polarization Method:

Mating end

Connector Locking Method:

Jackscrew

End Application:

An/spn-35c, radar and iff systems

Operating Temperature Rating:

Between -55.0 degrees celsius and 200.0 degrees celsius

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Beryllium single mating end single contact grouping and copper single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

Insert Material:

Plastic acrylic single mating end

Terminal Type:

Solder well single mating end single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium

Included Contact Quantity:

15 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact plating gold

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0