## NSN 5935-01-507-3586

Electrical Connector Backshell - Page 1 of 2



| <u> </u>  |
|---|
| View Online at https://aerobasegroup.com/nsn/5935-01-507-3586             |
| Thread Class:   |
| 2a  |
| Thread Direction:   |
| Right-hand  |
| Overall Length:   |
| 0.925 inches  |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 0.715 inches  |
| Overall Height:   |
| 1.030 inches  |
| Overall Width:  |
| 0.360 inches  |
| End Application:  |
| An/spn-35c, radar and iff systems   |
| Cable Opening Diameter:   |
| 0.250 inches  |
| Cable Opening Quantity:   |
| 1   |
| Size Designation:   |
| 15  |
| Mounting Facility Type And Quantity:                                      |
| 2 jackscrew   |
| Features Provided:  |
| Electromagnetic interference shielding                                    |
| Thready Qty Per Inch (tpi):   |
| 56  |
| Thread Size:  |
| 0.086 inches  |
| Special Features:   |
| Backshell's cable entry collar is at 45 degrees                           |
| Material:   |
| Aluminum  |
| Surface Treatment:  |
| Nickel  |
| Style Designator:   |
| Hood, side opening w/jackscrew  |
| Supplementary Features:   |
| Jackscrews are male with fillister heads                                  |
| Surface Treatment:  |
| Nickel, electroless   |
| Thread Series Designator:   |

Unc

## NSN 5935-01-507-3586

Electrical Connector Backshell - Page 2 of 2



| _ |     |      |   |        |  |
|---|-----|------|---|--------|--|
| c | hο  | JIF. |   | .ife:  |  |
| J | 116 |      | _ | .II C. |  |

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A10100