## NSN 5935-01-507-4270

Thread Class: 2a and 2b

**Body Style:** 

**Thread Direction:** 

Right-hand and right-hand

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-507-4270

Straight shape, internal coupling w/strain relief **Body Length:** 2.812 inches **Overall Diameter:** 1.513 inches **Cable Entrance Diameter:** Between 0.348 inches and 0.626 inches **Threaded Device Type:** Back shell and coupling facility **Mating End Quantity: Contact Position Arrangement Style:** 19-42 single mating end **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Key or multiple key **Insert Position In Deg:** 0.0 and 135.0 and 170.0 and 200.0 and 310.0 Shell Type: Split **Connector Locking Method:** Internally threaded coupling ring **Connector Cable Strain Relief Method:** Cable clamp **End Application:** Seawolf class ssn, panel, cargo Thready Qty Per Inch (tpi): 18 and 10 **Thread Size:** 1.250 inches and 1.312 inches **Terminal Location:** Back single mating end single contact grouping **Terminal Type:** Crimp single mating end single contact grouping **Shell Material:** Aluminum

## **NSN 5935-01-507-4270**Electrical Plug Connector - Page 2 of 2



Shell Surface Treatment:
Cadmium
Included Contact Quantity:
42 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Special Features:
Contacts per mil-c-39029/83-508
Color:
Olive drab
Precious Material And Location:
Contact surfaces gold
Precious Material:
Gold
Test Data Document:
81349-mil-c-28840 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Unef and double stub
Specification Data:
81349-mil-c-28840/17 government specification
Shelf Life:
N/a
Unit Of Measure:
<del>-</del>
Demilitarization:
No
Fiig:
A039b0