## NSN 5935-01-507-4274

Thread Class: 2a and 2b

**Body Style:** 

**Thread Direction:** 

Right-hand and right-hand

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-507-4274

Straight shape, internal coupling w/strain relief **Body Length:** 2.812 inches **Overall Diameter:** 1.513 inches **Cable Entrance Diameter:** Between 0.348 inches and 0.626 inches **Threaded Device Type:** Back shell and coupling facility **Mating End Quantity: Contact Position Arrangement Style:** 19-42 single mating end **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Key or multiple key **Insert Position In Deg:** 0.0 and 49.0 and 169.0 and 200.0 and 244.0 Shell Type: Split **Connector Locking Method:** Internally threaded coupling ring **Connector Cable Strain Relief Method:** Cable clamp **End Application:** Seawolf class ssn, panel, cargo Thready Qty Per Inch (tpi): 18 and 10 **Thread Size:** 1.250 inches and 1.312 inches **Terminal Location:** Back single mating end single contact grouping **Terminal Type:** Crimp single mating end single contact grouping **Shell Material:** Aluminum

## **NSN 5935-01-507-4274**Electrical Plug Connector - Page 2 of 2



Cadmium Included Contact Quantity:  42 single mating end single contact grouping Included Contact Type: Round pin single mating end single contact grouping Special Features: Contacts per mil-c-39029/83-508 Color: Color:	
42 single mating end single contact grouping Included Contact Type: Round pin single mating end single contact grouping Special Features: Contacts per mil-c-39029/83-508 Color:	
Included Contact Type:  Round pin single mating end single contact grouping  Special Features:  Contacts per mil-c-39029/83-508  Color:	
Round pin single mating end single contact grouping  Special Features:  Contacts per mil-c-39029/83-508  Color:	
Special Features: Contacts per mil-c-39029/83-508 Color:	
Contacts per mil-c-39029/83-508	
Color:	
Olive drab	
Precious Material And Location:	
Contact surfaces gold	
Precious Material:	
Gold	
Test Data Document:	
31349-mil-c-28840 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in spe	cification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on cer	tain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).	
Thread Series Designator:	
Unef and double stub	
Specification Data:	
31349-mil-c-28840/17 government specification	
Shelf Life:	
N/a	
Unit Of Measure:	
-	
Demilitarization:	
No	
Filg:	
4039b0	