Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-507-4310

| Thread Class: |
|---|
| 2a |
| Thread Direction: |
| Right-hand |
| Body Style: |
| Straight shape, external coupling |
| Overall Length: |
| 1.625 inches |
| Overall Height: |
| Between 2.118 inches and 2.158 inches |
| Overall Width: |
| Between 2.118 inches and 2.158 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Height: |
| 1.568 inches |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: |
| 1.568 inches |
| Distance From Mounting Shoulder To Front Face: |
| Between 0.878 inches and 0.898 inches |
| Threaded Device Type: |
| Coupling facility |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| 29-121 single mating end |
| Contact Removability: |
| Removable single mating end single contact grouping |
| Polarization Method: |
| Keyway or multiple keyway |
| Insert Position In Deg: |
| 0.0 and 50.0 and 160.0 and 190.0 and 225.0 |
| Shell Type: |
| Split |
| Connector Locking Method: |
| Externally threaded shell |
| End Application: |
| Seawolf class ssn, panel cargo |
| Thready Qty Per Inch (tpi): |
| 10 |
| Thread Size: |
| 1.812 inches |
| Terminal Location: |
| Back single mating end single contact grouping |



Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Aluminum

Shell Surface Treatment:

Cadmium

Included Contact Quantity:

121 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Color:

Olive drab

Precious Material And Location:

Contact surfaces gold

Precious Material:

Gold

Test Data Document:

81349-mil-c-28840 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Double stub

Specification Data:

81349-mil-c-28840/12 government specification

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0