Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-507-4371

## Thread Class:

2b

Thread Direction:

Right-hand and right-hand

# Body Style:

Straight shape, internal coupling

#### Overall Length:

33.1 millimeters

#### **Overall Diameter:**

48.0 millimeters

#### **Environmental Protection:**

Corrosion resistant and fungus resistant and moisture resistant and salt spray proof and shock resistant and vibration resistant and weather resistant

# Threaded Device Type:

Back shell and coupling facility

# Mating End Quantity:

1

**Contact Position Arrangement Style:** 

Avca 25-19 single mating end

#### **Contact Removability:**

Removable single mating end single contact grouping

#### **Polarization Method:**

Key or multiple key

**Insert Position In Deg:** 

0.0 and 80.0 and 142.0 and 196.0 and 293.0

## Shell Type:

Solid

**Connector Locking Method:** 

Internally threaded coupling ring

#### **End Application:**

Aircraft, hawkeye e-2c

#### **Operating Tempurature Rating:**

Between -65.0 degrees celsius and 175.0 degrees celsius

#### **Thread Size:**

37.0 millimeters and 1.625 inches

#### **Terminal Location:**

Back single mating end single contact grouping

#### **Terminal Type:**

Crimp single mating end single contact grouping

#### **Shell Material:**

Plastic

#### Shell Surface Treatment:

Cadmium

# NSN 5935-01-507-4371

Electrical Plug Connector - Page 2 of 2



**Thread Tolerance Class:** 

6g external

**Included Contact Quantity:** 

19 single mating end single contact grouping

## Included Contact Type:

Round socket single mating end single contact grouping

## **Special Features:**

Contacts per mil-c-39029/106-617 which will withstand 1500 cycles of durability

#### Color:

Olive drab

# **Precious Material And Location:**

Contact surfaces gold and contact surfaces palladium

## **Precious Material:**

Gold and palladium

## Test Data Document:

81349-mil-dtl-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# **Thread Series Designator:**

Iso m and special acme

Specification Data:

81349-mil-dtl-38999/26 government specification

# Shelf Life:

N/a

#### Unit Of Measure:

--

#### **Demilitarization:**

No

## Fiig:

A039b0