NSN 5935-01-507-8636

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-507-8636

Thread Class:
2a and 2b
Thread Direction:
Right-hand and right-hand
Body Style:
Straight shape, internal coupling w/strain relief
Body Length:
6.500 inches
Overall Diameter:
1.281 inches
Environmental Protection:
Corrosion resistant and fungus resistant and salt water resistant and shock resistant and vibration resistant and weather resistant
Cable Entrance Diameter:
Between 0.344 inches and 0.562 inches
Threaded Device Type:
Back shell and coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
Ahev 11-7 single mating end
Contact Removability:
Removable single mating end single contact grouping
Polarization Method:
Key or multiple key
Insert Position In Deg:
0.0 and 90.0 and 145.0 and 195.0 and 252.0
Shell Type:
Split
Connector Locking Method:
Internally threaded coupling ring
Connector Cable Strain Relief Method:
Cable clamp
Thready Qty Per Inch (tpi):
20 and 10
Thread Size:
0.750 inches and 0.750 inches
Terminal Location:
Back single mating end single contact grouping
Terminal Type:

Shell Material:

Aluminum

Crimp single mating end single contact grouping

NSN 5935-01-507-8636Electrical Plug Connector - Page 2 of 2



Shell Surface Treatment:
Cadmium
Included Contact Quantity:
7 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Special Features:
Contacts per mil-c-39029/83-450
Color:
Olive drab
Precious Material And Location:
Contact surfaces gold
Precious Material:
Gold
Test Data Document:
81349-mil-dtl-28840 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Unef and double stub
Specification Data:
81349-mil-dtl-28840/26 government specification
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
A039b0