Electrical Connector Backshell - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5935-01-508-4566

| | ine at https://aerobasegroup.com/nsn/5935-01-508-4566 |
|----------------------|--|
| Thread D | Direction: |
| Right-har | nd |
| Overall V | Vidth: |
| 0.625 inc | hes |
| Body An | gle In Deg: |
| 90.0 | |
| Cable Op | pening Diameter: |
| 0.500 inc | hes |
| Size Des | ignation: |
| 23 | |
| Mounting | g Facility Type And Quantity: |
| 1 threade | ed coupling |
| Thread S | Size: |
| 37.0 milli | neters |
| Thread F | Pitch In Millimeters: |
| 1.00 | |
| Thread T | olerance Class: |
| 6h interna | al |
| Product | Name: |
| Adapter, | banding |
| Special F | Features: |
| Aluminun | n alloy adapter, elbow, coupling nut aluminum alloy; silicone o-ring |
| Material: | |
| Aluminun | n alloy |
| Surface ⁻ | Treatment: |
| Cadmium | and nickel |
| Style De | signator: |
| Angle typ | e |
| Surface [·] | Treatment: |
| Cadmium | and nickel, electroless |
| Thread S | Series Designator: |
| lso m | |
| Shelf Life | ə: |
| N/a | |
| Unit Of M | leasure: |
| | |
| Demilita | ization: |
| No | |
| Fiig: | |
| A10100 | |