

View Online at <https://aerobasegroup.com/nsn/5935-01-509-0417>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Body Style:**

Straight shape, internal coupling

**Overall Length:**

1.420 inches

**Overall Diameter:**

1.777 inches

**Environmental Protection:**

Corrosion resistant and fungus resistant and solvent resistant and vibration resistant and weather resistant

**Threaded Device Type:**

Back shell

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

24-61 single mating end

**Contact Removability:**

Removable single mating end single contact grouping

**Polarization Method:**

Key or multiple key

**Insert Position In Deg:**

90.0

**Shell Type:**

Solid

**Connector Locking Method:**

Bayonet shell

**Thready Qty Per Inch (tpi):**

18

**Thread Size:**

1.437 inches

**Terminal Location:**

Back single mating end single contact grouping

**Terminal Type:**

Crimp single mating end single contact grouping

**Shell Material:**

Aluminum alloy

**Shell Surface Treatment:**

Anodize

**Included Contact Quantity:**

61 single mating end single contact grouping

**Included Contact Type:**

Round pin single mating end single contact grouping

**Special Features:**

Contacts per mil-c-39039/4-110

**Color:**

Black

**Precious Material And Location:**

Contact surfaces gold

**Precious Material:**

Gold

**Test Data Document:**

81349-mil-c-26482 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Unef

**Specification Data:**

96906-ms3476 government standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-c-26482 spec.